

Features: **R-410A** / **R-22** REFRIGERANT REFRIGERANT

- Auto air swing
- 24V signal control
- Wireless remote control
- Wired remote control (optional)
- Detachable and washable grille
- Durable washable filter
- R-410A / R-22 refrigerant



TECHNICAL SPECIFICATIONS

Model		CF41C-024-M3H1C	CF41C-036-M3H1C	CF41C-048-M3H1C	CF41C-060-M3H1C
Power supply		208/230V/1/ 60Hz			
Cooling capacity	Btu/h	24,000	36,000	48,000	60,000
Air flow volume	m3/h	1200	1400	2200	2100
	CFM	706	824	1295	1236
Rated current	A	0.65	0.65	1.6	1.6
Sound pressure level	dB(A)	50	52	58	58
Connecting pipe diameter (Gas)	Inches	5/8	3/4	7/8	7/8
Connecting pipe diameter (liquid)	Inches	3/8	3/8	3/8	1/2
Net Weight	kg/Lb	41/90.4	41/91	50/110	50/110
Gross weight	kg/Lb	50/110	50/111	59/130	59/130
Dimensions (W x H x D)	mm	48x27x9		56x27x10	
Packing dimensions (W x H x D)	inches	53x32x12		13x61x33	
Container loading quantity	40'GP/40' HC	132/132		90/90	



Carrier InterAmerica Corporation
Miami, Florida USA
www.ciac-comfort.com

Authorized Dealer: